

**FACTORY :** Survey No.322/3, AT-Indrad, TA-Kadi,  
Dist-Mehsana-382715. Gujarat.(INDIA)

**OFFICE :** 4,Shreenath Bunglows,  
Ramwadi Tekra, Isanpur, Ahmedabad-382443.

**E mail :** info@siliconindustries.net

**Website :** www.siliconindustries.net

# **BARIUM CHLORIDE DIHYDRATE**

## **MSDS MATERIAL SAFETY DATA SHEET**

### **01: PRODUCT IDENTIFICATION**

**SYNONYMS :** BARIUM DICHLORIDE

**CAS NO. :** 10361-37-2

**MOLECULAR WEIGHT :** 208.27

**CHEMICAL FORMULA :** BaCl<sub>2</sub>

**PRODUCT CODES :** 0980

### **02: COMPOSITION/INFORMATION ON INGREDIENTS**

INGREDIENT	CAS NO	PERCENT	HAZARDOUS
BARIUM CHLORIDE	10361-37-2	98 – 99.5 %	YES

### **03: COMPOSITION/INFORMATION ON INGREDIENTS**

#### **EMERGENCY OVERVIEW**

**DANGER! MAY BE FATAL IF SWALLOWED. HARMFUL IF INHALED. MAY CAUSE IRRITATION TO SKIN, EYES, AND RESPIRATORY TRACT. AFFECTS HEART, RESPIRATORY SYSTEM, AND CENTRAL NERVOUS SYSTEM.**

#### **SAF-T-DATA(TM) RATINGS (PROVIDED HERE FOR YOUR CONVENIENCE)**

**HEALTH RATING:** 3 - Severe (Poison)

**FLAMMABILITY RATING:** 0 - None

**REACTIVITY RATING:** 1 - Slight

**CONTACT RATING:** 2 - Moderate

**LAB PROTECTIVE EQUIP:** GOGGLES; LAB COAT; VENT HOOD; PROPER GLOVES

**STORAGE COLOR CODE:** Blue (Health)

#### **POTENTIAL HEALTH EFFECTS**

##### **INHALATION:**

Irritates the respiratory tract. May produce sore throat, coughing and labored breathing. Other symptoms may parallel ingestion.

##### **INGESTION:**

**FACTORY :** Survey No.322/3, AT-Indrad, TA-Kadi,  
Dist-Mehsana-382715. Gujarat.(INDIA)

**OFFICE :** 4,Shreenath Bunglows,  
Ramwadi Tekra, Isanpur, Ahmedabad-382443.

**E mail :** info@siliconindustries.net

**Website :** www.siliconindustries.net

**SILICON**  
**INDUSTRIES**

Manufacturer : Inorganic Chemicals | Barium Salts

**Toxic!** May cause severe gastroenteritis, including abdominal pain, vomiting and diarrhea. May cause tremors, faintness, paralysis of arms and legs, and slow or irregular heartbeat. Severe cases may produce collapse and death on respiratory failure. Estimated lethal dose in humans: 1 gram.

**SKIN CONTACT:**

May cause irritation with redness and pain.

**EYE CONTACT:**

May cause irritation, redness, pain, or blurred vision.

**CHRONIC EXPOSURE:**

No information found.

**AGGRAVATION OF PRE-EXISTING CONDITIONS:**

Persons with pre-existing skin disorders or impaired respiratory function may be more susceptible to the effects of the substance.

#### 04: FIRST AID MEASURES

**INHALATION:**

Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Call a physician.

**INGESTION:**

Get medical attention immediately. Induce vomiting immediately as directed by medical personnel. Never give anything by mouth to an unconscious person. After vomiting, a mixture of 1 tablespoon of sodium or magnesium sulfate (Epsom salts) dissolved in 8 oz. of water to drink maybe indicated to precipitate the barium as the nontoxic and insoluble barium sulfate.

**SKIN CONTACT:**

Remove any contaminated clothing. Wash skin with soap and water for at least 15 minutes. Get medical attention if irritation develops or persists.

**EYE CONTACT:**

Immediately flush eyes with plenty of water for at least 15 minutes, lifting upper and lower eyelids occasionally. Get medical attention if irritation persists.

**NOTE TO PHYSICIAN:**

Monitor patients with significant ingestion for respiratory, cardiovascular, and blood pressure status. Watch for cardiac arrhythmias, respiratory failure due to flaccid paralysis of respiratory muscles, pulmonary edema, vocal cord paralysis, severe hypertension, and late effect kidney failure. Acute barium poisoning results in hypokalemia. The administration of fluids containing dilute concentrations of potassium salts may be indicated.

#### 05: FIRE FIGHTING MEASURES

**FACTORY :** Survey No.322/3, AT-Indrad, TA-Kadi,  
Dist-Mehsana-382715. Gujarat.(INDIA)

**OFFICE :** 4,Shreenath Bunglows,  
Ramwadi Tekra, Isanpur, Ahmedabad-382443.

**E mail :** info@siliconindustries.net

**Website :** www.siliconindustries.net

**FIRE:**

Not considered to be a fire hazard.

**EXPLOSION:**

Not considered to be an explosion hazard.

**FIRE EXTINGUISHING MEDIA:**

Use any means suitable for extinguishing surrounding fire.

**SPECIAL INFORMATION:**

In the event of a fire, wear full protective clothing and NIOSH-approved self-contained breathing apparatus with full facepiece operated in the pressure demand or other positive pressure mode.

## 06: ACCIDENTAL RELEASE MEASURES

Ventilate area of leak or spill. Wear appropriate personal protective equipment as specified in Section 8. Spills: Sweep up and containerize for reclamation or disposal. Vacuuming or wet sweeping may be used to avoid dust dispersal.

## 07: ACCIDENTAL RELEASE MEASURES

Keep in a tightly closed container. Protect from physical damage. Store in a cool, dry, ventilated area away from sources of heat, moisture and incompatibilities. Containers of this material may be hazardous when empty since they retain product residues (dust, solids); observe all warnings and precautions listed for the product.

## 08: EXPOSURE CONTROLS/PERSONAL PROTECTION

**AIRBORNE EXPOSURE LIMITS:**

For Soluble Barium Compounds:

OSHA Permissible Exposure Limit (PEL):

0.5 mg (Ba)/m<sup>3</sup>

ACGIH Threshold Limit Value (TLV):

0.5 mg (Ba)/m<sup>3</sup> A4 - not classifiable as a human carcinogen

**VENTILATION SYSTEM:**

A system of local and/or general exhaust is recommended to keep employee exposures below the Airborne Exposure Limits. Local exhaust ventilation is generally preferred because it can control the emissions of the contaminant at its source, preventing dispersion of it into the general work area. Please refer to the ACGIH document, Industrial Ventilation, A Manual of Recommended Practices, most recent edition, for details

**FACTORY :** Survey No.322/3, AT-Indrad, TA-Kadi,  
Dist-Mehsana-382715. Gujarat.(INDIA)

**OFFICE :** 4,Shreenath Bunglows,  
Ramwadi Tekra, Isanpur, Ahmedabad-382443.

**E mail :** info@siliconindustries.net

**Website :** www.siliconindustries.net

**SILICON**  
**INDUSTRIES**

Manufacturer : Inorganic Chemicals | Barium Salts

### PERSONAL RESPIRATORS (NIOSH APPROVED):

If the exposure limit is exceeded and engineering controls are not feasible, a half facepiece particulate respirator (NIOSH type N95 or better filters) may be worn for up to ten times the exposure limit or the maximum use concentration specified by the appropriate regulatory agency or respirator supplier, whichever is lowest.. A full-face piece particulate respirator (NIOSH type N100 filters) may be worn up to 50 times the exposure limit, or the maximum use concentration specified by the appropriate regulatory agency, or respirator supplier, whichever is lowest. If oil particles (e.g. lubricants, cutting fluids, glycerine, etc.) are present, use a NIOSH type R or P filter. For emergencies or instances where the exposure levels are not known, use a full-facepiece positive-pressure, air-supplied respirator. **WARNING:** Air-purifying respirators do not protect workers in oxygen-deficient atmospheres.

### SKIN PROTECTION:

Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

### EYE PROTECTION:

Use chemical safety goggles. Maintain eye wash fountain and quick-drench facilities in work area.

## 09: EXPOSURE CONTROLS/PERSONAL PROTECTION

### APPEARANCE:

Colorless, flat crystals.

### ODOR:

Odorless.

### SOLUBILITY:

31 g/100 g water @ 0C (32F)

### SPECIFIC GRAVITY:

3.86 @ 24C(75F)

### pH:

No information found.

### % Volatiles by volume @ 21C (70F):

0

### BOILING POINT:

1560C (2840F)

### MELTING POINT:

963C (1765F)

### VAPOR DENSITY (AIR=1):

No information found.

### VAPOR PRESSURE (MM HG):

No information found.

### EVAPORATION RATE (BUAC=1):

**FACTORY :** Survey No.322/3, AT-Indrad, TA-Kadi,  
Dist-Mehsana-382715. Gujarat.(INDIA)

**OFFICE :** 4,Shreenath Bunglows,  
Ramwadi Tekra, Isanpur, Ahmedabad-382443.

**E mail :** info@siliconindustries.net

**Website :** www.siliconindustries.net

No information found.

## 10: STABILITY AND REACTIVITY

### STABILITY:

Stable under ordinary conditions of use and storage.

### HAZARDOUS DECOMPOSITION PRODUCTS:

Oxides of the contained metal and halogen, possibly also free, or ionic halogen.

### HAZARDOUS POLYMERIZATION:

Will not occur.

### INCOMPATIBILITIES:

Bromine trifluoride; 2-furan percarboxylic acid.

### CONDITIONS TO AVOID:

Incompatibles.

## 11: STABILITY AND REACTIVITY

Barium chloride (anhydrous): Oral rat LD50: 118 mg/kg. Investigated as a mutagen and reproductive effector.

-----\Cancer Lists\-----

Ingredient	Known	Anticipated	IARC Category
Barium Chloride (10361-37-2)	No	No	None

## 12: ECOLOGICAL INFORMATION

### ENVIRONMENTAL FATE:

This material is expected to significantly bioaccumulate.

### ENVIRONMENTAL TOXICITY:

No information found.

## 13: DISPOSAL CONSIDERATIONS

Whatever cannot be saved for recovery or recycling should be handled as hazardous waste and sent to a RCRA approved incinerator or disposed in a RCRA approved waste facility. Processing, use or contamination of this product may change the waste management options. State and local disposal regulations may differ from federal disposal regulations. Dispose of container and unused contents in accordance with federal, state and local requirements.

**FACTORY :** Survey No.322/3, AT-indrad, TA-Kadi,  
Dist-Mehsana-382715. Gujarat.(INDIA)

**OFFICE :** 4,Shreenath Bunglows,  
Ramwadi Tekra, Isanpur, Ahmedabad-382443.

**E mail :** info@siliconindustries.net

**Website :** www.siliconindustries.net

 **SILICON**  
INDUSTRIES

Manufacturer : Inorganic Chemicals | Barium Salts

## 14: Transport Information

### DOMESTIC (LAND, D.O.T.)

#### PROPER SHIPPING NAME:

BARIUM COMPOUND, N.O.S. (BARIUM CHLORIDE)

#### HAZARD CLASS:

6.1

#### UN/NA:

UN1564

#### PACKING GROUP:

III

(Information reported for product/size: 2.5KG)

### INTERNATIONAL (WATER, I.M.O.)

#### PROPER SHIPPING NAME:

BARIUM COMPOUND, N.O.S. (BARIUM CHLORIDE)

#### HAZARD CLASS:

6.1

#### UN/NA:

UN1564

#### PACKING GROUP:

III

(Information reported for product/size: 2.5KG)

### INTERNATIONAL (AIR, I.C.A.O.)

#### PROPER SHIPPING NAME:

BARIUM COMPOUND, N.O.S. (BARIUM CHLORIDE)

#### HAZARD CLASS:

6.1

#### UN/NA:

UN1564

#### PACKING GROUP:

III

(Information reported for product/size: 2.5KG)

## 15: OTHER INFORMATION

#### NFPA RATINGS: HEALTH:

3 Flammability: 0 Reactivity: 0

#### LABEL HAZARD WARNING:

**FACTORY :** Survey No.322/3, AT-indrad, TA-Kadi,  
Dist-Mehsana-382715. Gujarat.(INDIA)

**OFFICE :** 4,Shreenath Bunglows,  
Ramwadi Tekra, Isanpur, Ahmedabad-382443.

**E mail :** info@siliconindustries.net

**Website :** www.siliconindustries.net



Manufacturer : Inorganic Chemicals | Barium Salts

**DANGER! MAY BE FATAL IF SWALLOWED. HARMFUL IF INHALED. MAY CAUSE IRRITATION TO SKIN, EYES, AND RESPIRATORY TRACT. AFFECTS HEART, RESPIRATORY SYSTEM, AND CENTRAL NERVOUS SYSTEM.**

**LABEL PRECAUTIONS:**

- Avoid contact with eyes, skin and clothing.
- Avoid breathing dust.
- Keep container closed.
- Use with adequate ventilation.
- Wash thoroughly after handling.

**LABEL FIRST AID:**

If swallowed, induce vomiting immediately as directed by medical personnel. Never give anything by mouth to an unconscious person. Call a physician immediately. If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Call a physician. In case of contact, immediately flush eyes or skin with plenty of water for at least 15 minutes. Get medical attention if irritation develops.

**PRODUCT USE:**

Laboratory Reagent.

**REVISION INFORMATION:**

MSDS Section(s) changed since last revision of document include: 3, 14.

**Key Tags:**

barium chloride anhydrous msds

barium chloride anhydrous formula

**BaCl<sub>2</sub>**

Barium chloride anhydrous | Barium chloride Application | Silicon